

MOTOR SPECIFICATION SHEET

MODEL : CNHM2-6120-25 (LT) (Motor model : SF-JRG 2HP 4P)

USED FOR : GEAR MOTOR

| DESCRIPTION | DETAIL | | | | |
|------------------------------------|---|-----|-----|-----|-----|
| PHASE | 3 | | | | |
| MODEL NAME | CNHM2-6120-25 | | | | |
| RATED OUTPUT, HP (kW) | 2 (1.5) | | | | |
| POLE | 4 | | | | |
| CODE | MEATH CODE : 1G1025-020N61201 | | | | |
| OUTLINE DRAWING NO. | OMM94O966-* | | | | |
| RATED VOLTAGE (V) | 220 | 380 | 415 | 220 | 440 |
| RATED FREQUENCY (Hz) | 50 | 50 | 50 | 60 | 60 |
| RATED CURRENT (A) | 5.9 | 3.4 | 3.4 | 5.5 | 3.1 |
| RATED SPEED (min ⁻¹) * | 57 | 57 | 58 | 68 | 69 |
| THERMAL CLASS | 155(F) | | | | |
| RATING | S1 (CONTINUOUS) | | | | |
| ENCLOSURE CONSTRUCTION | TOTALLY ENCLOSED FAN COOLED | | | | |
| DEGREES OF PROTECTION | IP55 | | | | |
| METHOD OF COOLING | IC411 | | | | |
| FRAME NO. | 90L | | | | |
| WEIGHT (kg) | 41 | | | | |
| STANDARD | IEC 60034-1, JEC-2137-2000 | | | | |
| INSTALLATION | FOOT MOUNTED | | | | |
| ROTATION | CCW (VIEWED FROM SHAFT END) | | | | |
| BEARING | LOAD SIDE : 6205ZZ | | | | |
| | OPPOSITE SIDE : 6204ZZ | | | | |
| BEARING GREASE | UREA GREASE | | | | |
| CIRCUMSTANCE CONDITION | AMBIENT TEMPERATURE : -20 ~ +40°C | | | | |
| | AMBIENT HUMIDITY : 95%RH OR LESS | | | | |
| | ABOVE SEA LEVEL : 1000m OR LESS | | | | |
| | ENVIRONMENT : NO BURSTING/EROSIVE GAS OR VAPOR | | | | |
| COLOR | MUNSELL N5.5 (GRAY) | | | | |
| TERMINAL BOX | NO. OF LEAD WIRES : 6 | | | | |
| | SOURCE CONNECTION : TERMINAL BLOCK | | | | |
| INSULATION RESISTANCE | BY DC 500V MEGGER - ≥100MΩ | | | | |
| DIELECTRIC TEST | AC 50Hz 1800V - 1min. (Based on rated voltage 380V) | | | | |
| GEAR RATIO | 1 : 25 | | | | |
| GEAR LUBRICANT | GREASE (Filled from factory.) | | | | |
| SERVICE FACTOR | 2.06 | | | | |
| MATERIAL | FRAME : STEEL PLATE | | | | |
| | BRACKET (GEAR SIDE) : CAST IRON | | | | |
| | BRACKET (OPP SIDE) : ALUMINIUM | | | | |
| | GEAR CASE : CAST IRON | | | | |
| | SHAFT (MOTOR) : STEEL | | | | |
| | SHAFT (GEAR OUTPUT) : STEEL | | | | |
| | STATOR CORE : ELECTRICAL STEEL | | | | |
| | WIRE : ENAMELLED COPPER MAGNET WIRE | | | | |
| | INSULATOR : POLYESTER FILM | | | | |
| | VARNISH : EPOXY DENATURALIZATION POLYESTER | | | | |
| | ROTOR CORE : ELECTRICAL STEEL | | | | |
| | CONDUCTOR : ALUMINIUM | | | | |
| | TERMINAL BOX : STEEL PLATE | | | | |
| PAINTING : POLYURETHANE RESIN | | | | | |
| PRODUCTION COUNTRY | THAILAND | | | | |

* This value is calculated by MOTOR RATED SPEED / GEAR RATIO.

(Catalog value is specified by follow Gear maker specification, 50/60Hz = 58/70min⁻¹.)


Specifications subject to change without notice.

| SPECIFICATION SHEET NO. | | | | |
|-------------------------|--|--|--|--|
| SS-M-9388-A | | | | |

MODEL CNHM THREE PHASE INDUCTION MOTOR OUTLINE DRAWING

GEAR MOTOR
TOTALLY ENCLOSED FAN COOLED
DEGREES OF PROTECTION IP55
DUST & WATER JET PROOF

CUSTOMER _____
USER _____
FOR _____
CUSTOMER'S ORDER NO. _____
QUANTITY _____
MFG. ORDER NO. _____



SECTION A-A

| YOUR ORDER | MOTOR FRAME SIZE | RATING | TH. CLASS | AMB. TEMP | BEARINGS | | COLOR | DIRECTION OF ROTATION | NO. OF LEAD WIRES | REMARKS |
|------------|------------------|------------|-----------|-----------|-----------|-----------|---------------------|-----------------------|-------------------|---------|
| | | | | | LOAD SIDE | OPP. SIDE | | | | |
| | 90L | S1 (CONT.) | 155(F) | 40°C | 6205ZZ | 6204ZZ | GRAY (MUNSELL N5.5) | CCW | 6 | |

| YOUR ORDER | MODEL NAME | RATIO | SERVICE FACTOR | MOTOR OUTPUT | | POLE | HERTZ | VOLT | OUTPUT SPEED (rpm) | LUBRICATION TYPE | WEIGHT (kg) |
|------------|---------------|-------|----------------|--------------|-----|------|-------|-------------|--------------------|-----------------------|-------------|
| | | | | HP | kW | | | | | | |
| | CNHM2-6120-25 | 1:25 | 2.06 | 2 | 1.5 | 4 | 50 | 220/380/415 | 58 | GREASE ⁽¹⁾ | 41 |
| | | | | | | | 60 | 220/440 | 70 | | |
| | CNHM2-6120-29 | 1:29 | 1.91 | 2 | 1.5 | 4 | 50 | 220/380/415 | 50 | | |
| | | | | | | | 60 | 220/440 | 60 | | |
| | CNHM2-6120-35 | 1:35 | 1.58 | 2 | 1.5 | 4 | 50 | 220/380/415 | 41 | | |
| | | | | | | | 60 | 220/440 | 50 | | |
| | CNHM2-6125-43 | 1:43 | 1.56 | 2 | 1.5 | 4 | 50 | 220/380/415 | 34 | | |
| | | | | | | | 60 | 220/440 | 41 | | |

NOTE : (1) Grease had been filled from manufacturer already.

MITSUBISHI ELECTRIC AUTOMATION (THAILAND) CO., LTD.

| | | | |
|--|---------------------------------|---|------------------|
| | | OUTLINE DRAWING NO. OMM940966 | REV. * |
| | DIMENSION IN mm. SCALE : NTS | | |